

# **SAFETY DATA SHEET** Asia Pacific GHS Format

Print date: 26-Aug-2014

Revision Number: 1

Revision date: 25-Aug-2014

1. IDENT	TIFICATION OF THE SUBSTANCE AND COMPANY	
Trademark:	LEXAN™	
Product Code:	LUX2180T-11204	
Product Description:	Polycarbonate [CASRN 111211-39-3]	
Product Type:	Commercial Product	
Recommended use:	May be used to produce molded or extruded articles or as a component of other industrial products.	
Company:	<ul> <li>-SABIC Japan LLC.</li> <li>Tokyo Club Building, 2-6 3Chome Kasumigaseki, Chiyoda-Ku Tokyo, 100-0013 Japan</li> <li>-SABIC Innovative Plastics (China) Ltd.or SABIC Innovative Plastics International Tradir Shanghai Ltd. 2550 Xiupu Road, Pudong New Area, Shanghai 201319, China (Conact address)</li> <li>-SABIC Korea Ltd. 20F, Donghoon Building, 317, Teheran-ro, Seoul, Korea</li> <li>-SABIC Innovative Plastics Singapore Pte Ltd</li> <li>23, Benoi Road, 629895 Singapore</li> <li>-SABIC Innovative Plastics (Thailand) Co. Ltd</li> <li>64/22 Moo 4 Tumbol Pluak Daeng, Amphur Pluak Daeng,Rayong 21140 Thailand</li> <li>-SABIC Innovative Plastics India Ltd.</li> <li>Plastics Avenue, P.O. Jawaharnagar,District Vadodara 391320 India</li> <li>-SABIC Taiwan Holding Ltd, Taiwan Branch, Room B,7F,No. 8,Min-Sheng E. Rd. Sec. 3,Taipei City 10480 Taiwan</li> <li>-SABIC Innovative Plastics Hong Kong Limited.</li> <li>Flat/ RM 1701, Tower 1, The Gateway 25 Canton Road, Tsimshatsui, Hong Kong</li> </ul>	
Manufacturer:	SABIC Innovative Plastics China Co. Ltd. No: 1 Plastics Avenue, P.C. 511548 Western Ind. District, Nansha ETDZ, Pan Yu, Guanndong China	
Emergency Telephone Number:	Japan: +(81)-3-3593-4735 China: +86 532 83889090,+86 20 84980148 Korea: +(82)-2-510-6546 Singapore: +(65)-6210 4199 Thailand: +(66)-22312323-4 ext. 46, +(66)-38927000 ext. 7026 India: +(91)-265 3068554	
Emergency Transportation/CHEMTREC (24 HOUR):	800 424-9300 (USA) +1 703-527-3887 (globally, outside USA)	
· · · /	Asiaproductinquiries@sabic-ip.com	
E-mail:	Asiaproductinquiries@sabic-ip.com	



## 2. HAZARDS IDENTIFICATION

The additives in this product are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

### Globally Harmonized System, UN(GHS) - Classification

### **GHS Category**

Not hazardous

Not classified

### **GHS-Labeling**

GHS Labeling not required

### **Precautionary Statements**

No GHS specific Precautionary Statements required - observe all other warnings and handling instructions in this SDS.

### Other hazards which do not result in classification:

#### SABIC Emergency Overview

- Pellets with slight or no odor
- Spilled material may create slipping hazard
- Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information:	OSHA, IARC and/or NTP have listed carbon, titanium dioxide, crystalline silica (quartz), respirable glass and certain heavy metals, present in some colorants and fillers, as carcinogens. If these materials are present in this product at significant quantities, they are shown in Section 2/3. These materials are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions	
Processing Issues:	Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.	
Aggravated Medical Conditions:	MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to thi product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.	



## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### **Product Type**

Mixture

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

4. FIRST AID MEASURES		
If Inhalation:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If symptoms persist, call a physician.	
On skin contact:	Immediately cool the skin by rinsing with cold water after contact with hot material. Wash off immediately with soap and plenty of water. Consult a physician.	
On contact with eyes:	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists, consult a specialist.	
On ingestion:	No hazards which require special first aid measures.	
Precautions:	Processing vapors inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from the source of contamination or move victim to fresh air and obtain medical advice.	

**5. FIRE-FIGHTING MEASURES** 

Autoignition Temperature:	630°C (1166°F) estimated	
Explosive Limits uppe lower	•	Not determined Not determined
Suitable Extinguishing Media:	: Use dry chemical, CO2, water spray or "alcohol" foam. Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.).	
Unsuitable Extinguishing Media for Safety Reasons:	Do not use a solid water stream as it may scatter and spread fire.	
Hazards from Combustion Products:	Fire will produce dense black smoke containing hazardous combustion products, carbon oxides, hydrocarbon fragments.	
Specific Hazards:		res against static discharges. During processing, dust may form ermal decomposition can lead to release of irritating gases and
Special Protective Equipment for Firefighters:	and full protective equipme	but proper protection including self-contained breathing apparatus nt. Fight fire from a safe distance and a protected location due to vapors and decomposition products
Exposure hazards:	5	contaminated water into drains, soil or surface water. Sufficient retain the water used for extinguishing. Dispose of contaminated local regulations.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** 

See section 8.



Environmental Precautions:	Do not flush into surface water or sanitary sewer system. Material should not be released into the environment.	
Clean up:	Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by using a brush or compressed air.	
7. HANDLING AND STORAGE		

Handling:	Handle in accordance with good industrial hygiene and safety practices Provide for appropriate exhaust ventilation and dust collection at machinery Avoid dust formation All metal parts of the mixing and processing equipment must be earthed
Storage:	Store in closed container in a dry and cool area. Keep away from heat sources and sources of ignition. Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a dry and well-ventilated place.
Incompatible Products:	Strong acids, strong oxidizing agents.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits:	No components with information, unless noted below
------------------	--

\*SABIC Recommended Exposure Limits have been established for certain chemicals.

Engineering Measures to Reduce Exposure:	Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection.
Hand Protection:	Protective gloves should be worn
Eye Protection:	Safety glasses with side-shields or chemical goggles. In addition, use full-face shield when cleaning processing vapor condensates from hood, ducts, and other surfaces.
Respiratory Protection:	When using this product at elevated temperatures, implement engineering systems, administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid, gases, and particulate matter) if processing vapors are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.
Body Protection:	Long sleeved clothing
Hygiene Measures:	When using, do not eat, drink or smoke.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Appearance:	Pellets
Color:	Same as color code
Odor:	None or slight
Melting point/range:	This product does not exhibit a sharp melting point but softens gradually over a wide range of temperatures.
Flash Point:	Not applicable
Evaporation Rate:	Negligible



Explosive Limits upper: lower: Vapor Pressure: Specific gravity: Water Solubility: Autoignition Temperature: Explosive Properties: Oxidising Properties: VOC content (%):

Not determined Not determined Negligible >1; (water = 1) Insoluble 630°C (1166°F) estimated Dust may form explosive mixture in air Not oxidising Negligible

## **10. STABILITY AND REACTIVITY**

Reactivity:	Not reactive under recommended conditions of handling, storage, processing and use.
Stability:	Stable under ambient conditions. Hazardous polymerization does not occur.
Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	Avoid temperatures above 630°C. To avoid thermal decomposition, avoid elevated temperatures. Heating can result in the formation of gaseous decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended periods of time.
Materials to Avoid:	May react with strong oxidizing agents, strong acids or other highly reactive chemicals.
Hazardous Decomposition Products:	Process vapors under recommended processing conditions may include trace levels of hydrocarbons, phenols, alkylphenols, diarylcarbonates.

11. TO	XICOLOGICAL INFORMATION
Acute Toxicity	
Product Information:	
LD50/oral/rat: LD50/dermal/rabbit:	>5000 mg/kg >2000 mg/kg
Component Information:	
Component Information Text:	No data available
Sensitization	
Respiratory Sensitization:	Not classified
Irritation:	
Eye Irritation:	no data available
Primary Irritation:	Substance does not generally irritate and is only mildly irritating to the skin
Subchronic Toxicity (28 days)	

Product Name: LUX2180T-11204



Repeated Oral Toxicity(28d): Repeated Dermal Toxicity(28d Subchronic Toxicity:	):	No information available No Information available No information available
Chronic Toxicity Carcinogenicity:		There are no known carcinogenic chemicals in this product except specifically mentioned below.
Mutagenic Effects: Reproductive Toxicity: Developmental Toxicity:		No data is available on the product itself No information available No information available
Neurological effects:		No information available
Specific Target Organ Toxicity(STOT Target Organ Effects:	2	Not established
Aspiration Hazard Aspiration Hazard Statement:		No data available
Other relevant toxicity information IARC: OSHA: NTP:		Not listed Not regulated Not tested
Remarks:		The toxicological data has been taken from products of similar composition.
Special Studies:	No Information	
	12. ECOLOGICA	

### Ecotoxicity

**Component Information:** 

Product Information:

### Persistence and Degradability

Biodegradation: Partition coefficient (n-octanol/water)

#### Bioaccumulative Potential: Bioaccumulation:

Mobility Mobility:

Other Adverse Effects Ecotoxicity Effects: Not inherently biodegradable Not established

Not established

May be separated mechanically in waste water plants.

Do not flush into surface water or sanitary sewer system.

## **13. DISPOSAL CONSIDERATIONS**

**Waste from residues / unused** Where possible recycling is preferred to disposal or incineration. Dispose of in accordance with local regulations.



Contaminated Packaging:	Empty containers should be transported/delivered using a registered waste carrier for local recycling or waste disposal.
Waste Disposal:	Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

### **14. TRANSPORT INFORMATION**

IMO / IMDG	Not regulated
ICAO	Not regulated
IATA-DGR	Not regulated
DOT	Not regulated
ADR/RID	Not regulated
ADR	Not regulated
ADN	Not regulated

### **15. REGULATORY INFORMATION**

International Inventories:	
TSCA (USA):	Listed
DSL (Canada):	Listed
EINECS/ELINCS (Europe):	Listed
ENCS (Japan):	Listed
IECSC (China):	Listed
KECL (Korea):	Listed
PICCS (Philippines):	Listed
AICS (Australia):	Listed
NZIOC (New Zealand):	Listed

#### **Other Inventory Information:**

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

### SVHC (REACH Regulation (EC) No 1907/2006 and 453/2010, as amended):

This product does not intentionally contain SVHC chemicals except as noted below. Incidental amounts of impurities, if present, would be below the threshold limit of 0.1% by weight.

### SARA (313) Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA (311, 312) hazard class:	
Acute Health Hazard	N
Chronic Health Hazard	N



15. REG	<b>SULATORY INFORMATION</b>
Fire Hazard	Ν
Sudden Release of Pressure Hazard	Ν
Reactive Hazard	Ν

#### Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

### WHMIS hazard class:

Non-controlled

### California Proposition 65:

This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

### RoHS EU Directive 2002/95/EC (and its amendments and directive 2011/65/EU):

The subject product is in compliance with EU RoHS Directive 2002/95/EC (and its amendments and directive 2011/65/EU). All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

#### **Remarks:**

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

**HMIS Rating** 

Health: 0

Flammability: 1

Reactivity: 0



### **16. OTHER INFORMATION**

Brands marked with ® or <sup>™</sup> are trademarks of SABIC or affiliates

### SDS Scope:

China: Conforms to Chinese Regulation on the Control over Safety of Hazardous Chemicals (Decree No 591) and GHS standards GB15258, GB13698, GB/T16483 etc.

Japan: Conforms to Industrial Safety and Health Law, Japan (2006) and Industrial GHS Standards JIS Z7250, JIS Z7251 Korea: Conforms to Industrial Safety & Health Act, Ministry of Labor, Korea

Singapore: Conforms to Singapore workplace Safety and Health (WSH) Act, WSH Regulations, and GHS Standard 586 Taiwan: Conforms to Taiwan Rules on Hazard Communication and Labeling of Hazardous Substances, (Council of Labor Affairs, Taiwan) and GHS standards Z1051

Thailand: Conforms to Notification of the Ministry of Industry on the System of Classification and Hazard Communication of Hazardous Substances B.E. 2555 (2012)

This document is also applicable in other countries and regions.

### Prepared by: Product Stewardship & Toxicology

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

### End of Safety Data Sheet